Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

FAIRCHILD SEMICONDUCTOR®

Jameco Part Number 179303

TIP120/121/122

Medium Power Linear Switching Applications

- Complementary to TIP125/126/127



TO-220

1.Base 2.Collector 3.Emitter

NPN Epitaxial Darlington Transistor

Absolute Maximum Ratings T_C=25°C unless otherwise noted

Symbol	Parameter		Value	Units
V_{CBO}	Collector-Base Voltage	: TIP120	60	V
		: TIP121	80	V
		: TIP122	100	V
V_{CEO}	Collector-Emitter Voltage	: TIP120	60	V
		: TIP121	80	V
		: TIP122	100	V
V_{EBO}	Emitter-Base Voltage		5	V
I_C	Collector Current (DC)		5	A
I_{CP}	Collector Current (Pulse)		8	A
I_B	Base Current (DC)		120	mA
P_C	Collector Dissipation (T_a=25°C)		2	W
	Collector Dissipation (T_C=25°C)		65	W
T_J	Junction Temperature		150	°C
T_{STG}	Storage Temperature		- 65 ~ 150	°C

Equivalent Circuit



$R1 \cong 8\,k\Omega$
$R2 \cong 0.12\,k\Omega$

Electrical Characteristics T_C=25°C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Max.	Units
V_{CEO}(sus)	Collector-Emitter Sustaining Voltage				
	: TIP120	I_C = 100mA, I_B = 0	60		V
	: TIP121		80		V
	: TIP122		100		V
I_{CEO}	Collector Cut-off Current				
	: TIP120	V_{CE} = 30V, I_B = 0		0.5	mA
	: TIP121	V_{CE} = 40V, I_B = 0		0.5	mA
	: TIP122	V_{CE} = 50V, I_B = 0		0.5	mA
I_{CBO}	Collector Cut-off Current				
	: TIP120	V_{CB} = 60V, I_E = 0		0.2	mA
	: TIP121	V_{CB} = 80V, I_E = 0		0.2	mA
	: TIP122	V_{CB} = 100V, I_E = 0		0.2	mA
I_{EBO}	Emitter Cut-off Current	V_{BE} = 5V, I_C = 0		2	mA
h_{FE}	* DC Current Gain	V_{CE} = 3V,I_C = 0.5A	1000		
		V_{CE} = 3V, I_C = 3A	1000		
V_{CE}(sat)	* Collector-Emitter Saturation Voltage	I_C = 3A, I_B = 12mA		2.0	V
		I_C = 5A, I_B = 20mA		4.0	V
V_{BE}(on)	* Base-Emitter ON Voltage	V_{CE} = 3V, I_C = 3A		2.5	V
C_{ob}	Output Capacitance	V_{CB} = 10V, I_E = 0, f = 0.1MHz		200	pF

* Pulse Test : PW≤300μs, Duty cycle ≤2%

©2001 Fairchild Semiconductor Corporation

Typical characteristics



Figure 1. DC current Gain



Figure 2. Base-Emitter Saturation Voltage Collector-Emitter Saturation Voltage



Figure 3. Output and Input Capacitance vs. Reverse Voltage



Figure 4. Safe Operating Area



Figure 5. Power Derating

©2001 Fairchild Semiconductor Corporation

Package Demensions

TO-220



Dimensions in Millimeters

©2001 Fairchild Semiconductor Corporation

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FAST®	OPTOPLANAR™	STAR*POWER™
Bottomless™	FASTr™	PACMAN™	Stealth™
CoolFET™	FRFET™	POP™	SuperSOT™-3
CROSSVOLT™	GlobalOptoisolator™	Power247™	SuperSOT™-6
DenseTrench™	GTO™	PowerTrench®	SuperSOT™-8
DOME™	HiSeC™	QFET™	SyncFET™
EcoSPARK™	ISOPLANAR™	QS™	TruTranslation™
E^2CMOS™	LittleFET™	QT Optoelectronics™	TinyLogic™
EnSigna™	MicroFET™	Quiet Series™	UHC™
FACT™	MICROWIRE™	SLIENT SWITCHER®	UltraFET®
FACT Quiet Series™	OPTOLOGIC™	SMART START™	VCX™

STAR*POWER is used under license

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

©2001 Fairchild Semiconductor Corporation